



DATA SHEET

Electrical Data

Series	Power Rating	Primary Voltage 50-60 Hz	Temperature Rise	HiPot Testing	Short Circuit Proof "inherently limiting"	Approvals
SPK005	0.6 VA* * 60 Hz Rating	2 x 115 V	< 40°C, Class B130	5,000 V RMS	yes	none

Rated Voltage	SECONDARY RMS RATING				No-Load Voltage	PART NUMBER Dual Primary 2 x 115 V
	SERIES		PARALLEL			
	Voltage	Load mAmp.	Voltage	Load mAmp.		
2 x 6 V	12 V	50 mAmp.	6 V	100 mAmp.	9.0 V	SPK0050606-70002
2 x 9 V	18 V	33 mAmp.	9 V	66 mAmp.	13.6 V	SPK0050909-70002
2 x 12 V	24 V	25 mAmp.	12 V	50 mAmp.	18.1 V	SPK0051212-70002
2 x 15 V	30 V	20 mAmp.	15 V	40 mAmp.	22.5 V	SPK0051515-70002
2 x 18 V	36 V	16 mAmp.	18 V	33 mAmp.	27.0 V	SPK0051818-70002
2 x 24 V	48 V	12 mAmp.	24 V	25 mAmp.	36.3 V	SPK0052424-70002

Mechanical Data

