



DATA SHEET

Electrical Data

Series	Power Rating	Primary Voltage 50-60 Hz	Temperature Rise	HiPot Testing	Short Circuit Proof "inherently limiting"	Approvals
SPK020	2.0 VA* * 60 Hz Rating	115 V	< 40°C, Class B130	5,000 V RMS	yes	None

Rated Voltage	SECONDARY RMS RATING					PART NUMBER	
	SERIES		PARALLEL		No-Load Voltage	Primary 115 V	Primary 230 V
	Voltage	Load mAmp.	Voltage	Load mAmp.			
2 x 6 V	12 V	167mAmp.	6 V	333 mAmp.	9.6 V	SPK0200606-10002	not available
2 x 9 V	18 V	111mAmp.	9 V	222 mAmp.	14.4 V	SPK0200909-10002	
2 x 12 V	24 V	83 mAmp.	12 V	167 mAmp.	20.2 V	SPK0201212-10002	
2 x 15 V	30 V	66 mAmp.	15 V	133 mAmp.	24.0 V	SPK0201515-10002	
2 x 18 V	36 V	55 mAmp.	18 V	111 mAmp.	28.8 V	SPK0201818-10002	
2 x 24 V	48 V	42 mAmp.	24 V	83 mAmp.	38.4 V	SPK0202424-10002	

Mechanical Data

