



DATA SHEET



Electrical Data

Series	Power Rating	Primary Voltage 50-60 Hz	Temperature Rise	HiPot Testing	Short Circuit Proof "inherently limiting"	Approvals
SPK030	2.2 VA* * 60 Hz Rating	2 x 115 V	< 40°C, Class B130	5,000 V RMS	yes	None

Rated Voltage	SECONDARY RMS RATING				No-Load Voltage	PART NUMBER Dual Primary 2 x 115 V
	SERIES		PARALLEL			
	Voltage	Load mAmp.	Voltage	Load mAmp.		
2 x 6 V	12 V	183 mAmp.	6 V	366 mAmp.	9.6 V	SPK0300606-70002
2 x 9 V	18 V	122 mAmp.	9 V	244 mAmp.	14.4 V	SPK0300909-70002
2 x 12 V	24 V	92 mAmp.	12 V	183 mAmp.	19.2 V	SPK0301212-70002
2 x 15 V	30 V	73 mAmp.	15 V	147 mAmp.	24.0 V	SPK0301515-70002
2 x 18 V	36 V	61 mAmp.	18 V	122 mAmp.	28.8 V	SPK0301818-70002
2 x 24 V	48 V	45 mAmp.	24 V	92 mAmp.	38.6 V	SPK0302424-70002

Mechanical Data

